

# CARLOW CONCRETE TANKS

**DRAWING TITLE:**  
2.4m Ø x 5.6m  
PRECAST CONCRETE  
PUMP CHAMBER  
- TYPICAL DETAILS.

**Drawn By:** T. Armstrong  
**Date:** 30/09/09  
**Revision:** A

**TYPICAL INSITU CONCRETE SPECIFICATION:**  
CONCRETE GRADE: C28/35  
MIN. CEMENT CONTENT: 320 kg/m<sup>3</sup>  
MAX. W/C RATIO: 0.55  
MAX. AGGREGATE SIZE: 20mm  
STEEL FIBRE DOSAGE: 20 kg/m<sup>3</sup>  
STEEL FIBRE TYPE: DRAMIX RL 45/50 BN  
(OR SIMILAR)

**STANDARD LID DESIGN LOADS:**  
IMPOSED LOAD: 10 kN/m<sup>2</sup> UDL OR 5,850 kg WHEEL LOAD  
DEAD LOAD: UP TO 1m OVERBURDEN  
HEAVY DUTY OR CUSTOM LIDS CAN BE MANUFACTURED FOR  
MORE ONEROUS APPLICATIONS.

**STANDARD ACCESS OPENING SIZES:**  
- 1400mm x 850mm  
- 900mm x 600mm  
- 600mm x 600mm  
**NON STANDARD SIZES ARE AVAILABLE ON REQUEST**

